



## WP Synthetic Blend SAE 5W-20 Motor Oil

WP Synthetic Blend Motor Oil is formulated to provide wear protection and helps protect against the formation of sludge, varnish and rust.

<p><b>Performance, Features &amp; Benefits</b></p> <p>WP Synthetic Blend SAE 5W-20 is a synthetic blend multigrade motor oil formulated to:</p> <ul style="list-style-type: none"> <li>• Help reduce engine friction.</li> <li>• Protect against the formation of sludge, varnish and rust.</li> <li>• Protect against harmful deposits and acids, which aids in a clean running engine.</li> </ul> <p><b>Main Applications</b></p> <p>WP Synthetic Blend SAE 5W-20 Motor Oil is recommended for use in all vehicles requiring the use of SAE 5W-20 viscosity grade engine oils under all driving conditions.</p> <p>It can be mixed with other synthetic or mineral oils. Always consult your owner’s manual for the correct viscosity grade and performance recommendation required for your vehicle.</p>	<p><b>Specifications, Approvals &amp; Recommendations</b></p> <ul style="list-style-type: none"> <li>• General Motors GM 6094M</li> <li>• Chrysler MS 6395</li> <li>• Ford WSS-M2C945-A, M2C945-B1</li> </ul> <p>Exceeds the requirements of the following industry specifications:</p> <ul style="list-style-type: none"> <li>• API SP, API SP-Resource Conserving and all previous categories</li> <li>• ILSAC GF-6A</li> </ul> <p>Always follow manufacturer's recommendations and specifications for viscosity grade and API service.</p>
---	---

### Typical Physical Characteristics

Properties	Method	WP Synthetic Blend 5W-20 Motor Oil
KINEMATIC VISCOSITY @40°C cSt	ASTM D445	51.71
KINEMATIC VISCOSITY @100°C cSt	ASTM D445	8.71
VISCOSITY INDEX	ASTM D2270	149
DYNAMIC VISCOSITY @-30°C cP	ASTM D5293	5480
MRV @-35°C cP	ASTM D4684	18500
DENSITY @15°C Kg/m <sup>2</sup>	ASTM D4052	858.3
FLASH POINT °C	ASTM D92	226
FLASH POINT °C	ASTM D93	213
POUR POINT °C	ASTM D97	-48

These characteristics are typical of current production. Whilst future production will conform to manufacturers specification, variations in these characteristics may occur.



## Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from [www.WestPier.ca](http://www.WestPier.ca)

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your WestPier representative.