




WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil

WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil is an advanced proprietary formula with Active Cleansing Agents. Helps prevent dirt and contaminants from turning into performance robbing deposits. It meets or exceeds the engine protection required by ILSAC GF-6A, and GM dexos1™ specifications and is specially formulated to provide extra protection against the harmful effects of extreme driving conditions (stop-and-driving, short trips, extreme temperatures, idling, driving with weight).

<p>Performance, Features & Benefits</p> <p>WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil with Active Cleansing Agents:</p> <ul style="list-style-type: none"> • Superior for extreme driving conditions noted above then conventional oil • Formula provides added oxidation stability, improved volatility and low-temperate properties, and proven wear protection. • Assists in preventing sludge and other damaging deposits. <p>Main Applications</p> <p>WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil is recommended for use in all vehicles requiring the use of SAE 0W-20 viscosity grade engine oils under all driving conditions. WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil can also be mixed with other synthetic and mineral oils. Always consult your owner’s manual for correct viscosity grade and performance for older engines as this product may not be suitable for those applications.</p>	<p>Specifications, Approvals & Recommendations</p> <p>Meets or exceeds the requirements of the following industry specifications:</p> <ul style="list-style-type: none"> • Chrysler MS-6395 • Ford WSS-M2C962-A • API SP, API SP-Resource Conserving and all previous categories • ILSAC GF-6A and all previous ILSAC Standards • GM dexos1™ Gen 3 (License D335BADK403) <p>WP Evolution Full Synthetic SAE 0W-20 dexos 1 Gen 3 Motor Oil is designed to provide enhanced fuel economy and provides the same engine protection for use in vehicles currently using SAE 5W-20.</p> <p>Always follow manufacturer's recommendations and specifications for viscosity grade and API service.</p> <div style="text-align: center;">  </div>
---	--

Typical Physical Characteristics

Properties	Method	WP Evolution Full Synthetic SAE 0W-20 Dexos 1 Gen 3
Viscosity Grade	SAE J300	0W-20
Service Category		SP-RC
ILSAC		GF-6A
ACEA		N/A
Density	Kg/m ³ ASTM D4052	833
Flash Point	°C ASTM D93	241
Pour Point	°C ASTM D97	-48
Kinematic Viscosity @ 40°C	cSt ASTM D445	44.8
Kinematic Viscosity @ 100°C	cSt ASTM D445	8.4
Viscosity Index	ASTM D2270	165
CCS Viscosity @ -35°C	cP ASTM D5293	4 881
MRV Viscosity @ -40°C	cP ASTM D4684	14 900



These characteristics are typical of current production. Whilst future production will conform to manufacturers specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from www.WestPier.ca

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your WestPier representative.