



## WP Universal Tractor Hydraulic Fluid

**WP Universal Tractor Hydraulic Fluid** has been formulated from high quality base stocks and advanced additive technology. It is designed to lubricate common sump hydraulic, transmission, and final drive systems found in modern farm and construction equipment. **WP Universal Tractor Hydraulic Fluid** provides excellent wear protection and meets the latest requirements of many OEM tractor and transmission manufacturers.

### Performance, Features & Benefits

**WP Universal Tractor Hydraulic Fluid** has been designed to provide:

- All season performance
- Long fluid life
- Extreme pressure performance
- Filterability
- Wear protection
- Corrosion protection

#### **WP Universal Tractor Hydraulic Fluid:**

- Minimizes brake chatter without reducing brake capacity
- Is non-foaming

**Always follow OEM recommendations when it comes to setting drain intervals and for application requirements for your specific operations and equipment.**

### Main Applications

**WP Universal Tractor Hydraulic Fluid** is suitable for use in:

- Farm Equipment
- Construction Equipment
- Off Highway Equipment
- Industrial Tractors
- Powershift Transmissions
- Hydrostatic Transmissions
- Manual Transmissions
- Differentials
- Final Drives
- Wet Brakes
- Clutches
- Power Steering

### Specifications, Approvals & Recommendations

- Allison C-4
- API GL-4
- Caterpillar TO-2
- CNH MAT 3505
- CNH MAT 3525
- DEUTZ-AC POWER FLUID 821XL
- FIAT HESTON AF-87
- FORD ESN-M2C134-D
- INTERNATIONAL HARVESTER HY-TRAN B-6
- JICASE MS-1204, 1205, 1206, 1207, 1209, 1210
- JOHN DEERE JDM J20A AND J20C
- KOMATSU KES 07.866
- KUBOTA UDT
- LANDINI
- MASSEY-FERGUSON M1141, M1135, M1143, M1145
- NEW HOLLAND FNHA-2-C-200 (200")
- NEW HOLLAND FNHA-2-C-201 (134-D),
- NEW HOLLAND WB NWH 410B
- OLIVER/WHITE Q-1705, Q-1766B, TYPE 55, Q-1722, Q-1826
- RENK
- SAUER SUNSTRAND/DANFOSS & HYDRO STATIC TRANS FLUID
- SPERRY VICKERS ASTM D-2882 AND 35VQ25
- STEIGER
- VERSATILE
- VOLVO WB 101
- ZF TE-ML 03E, 05F, 17E



### Typical Physical Characteristics

Properties	WP Universal Tractor Hydraulic Fluid
VISCOSITY INDEX	151
KINEMATIC VISCOSITY @ 40 °C, CST	54.5
KINEMATIC VISCOSITY @ 100 °C, CST	9.2
GRAVITY, SPECIFIC	0.8600
FLASH POINT (COC) °F	400
POUR POINT °F	-38
BROOKFIELD VISCOSITY, @ -35°C, cP	34,000
ZINC, ppm	1388
FOAM TEST	PASS

These characteristics are typical of current production. Whilst future production will conform to manufacturers specification, variations in these characteristics may occur.

### Health, Safety & Environment

- **Health and Safety**

**WP Universal Tractor Hydraulic Fluid** is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from [www.WestPier.ca](http://www.WestPier.ca)

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

### Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your WestPier representative.